NOTICE TO BIDDERS FOR PURCHASE OF (3) DUMP TRUCKS AND (3) BEDS WITH SNOW PLOW EQUIPMENT SPECS ARE AVAILABLE ON PERRY COUNTY'S WEBSITE PERRY COUNTY INDIANA GOVERNMENT

Notice is hereby given that the Board of Commissioners of the County of Perry, Indiana, will receive sealed bids at the Perry County Auditor's Office, 2219 Payne Street, Tell City, IN 47586, up to the hour of 4:00 p.m. C.D.T. on Tuesday, October 21,2025. Bids will be opened sometime after 6:00 p.m. at the Board of Commissioners meeting on Tuesday, October 21, 2025.

All bids must comply with the Specifications and Instructions and in accordance with plans. Contract bidders may obtain copies of the Specifications and Instructions at www.perrycounty.in.gov or by contacting the Perry County Auditor's Office at 812-547-6427 located at: 2219 Payne Street, Tell City, IN 47586. Specifications will be available on September 29, 2025.

The Board of Commissioners reserves the right to accept the lowest or best bid for each separate bid item or to reject any and all bids.

Dated this 29th day of September, 2025.

Kristinia L. Hammack Perry County Auditor

Advertising Dates: September 29, 2025 and October 9, 2025

r.		



PALMER - KENWORTH OF EVANSVILLE (K081) 8516 BAUMGART ROAD EVANSVILLE, Indiana 47725 PERRY COUNTY HIGHWAY DEPARTMEN 17115 STATE ROUTE 37 LEOPOLD, Indiana 47551 United States of America

Clay Nall

Cell Phone: 812-454-5697 Office Phone: 812-867-7411 Email: cnall@palmertrucks.com STEVE HOWELL

Email: pchd@psci.net

Vehicle Summary

	Unit		Chassis	
Model:	T480 Series Conventi-	onal	Fr Axle Load (lbs):	14600
Type:	FULL TRU	JCK	Rr Axle Load (lbs):	23000
Description 1:	Perry County Hwy [Dept	G.C.W. (lbs):	60000
Description 2: T480	PX9 Allison S/A Snow Plow To	ruck		
	1/1/25	5 PL		
	Application		Road Conditions:	
Intended Serv.:	Snowplow: Vehicles which configu		Class A (Highway)	89
Commodity:	Gravel/Crushed Rock/S	Sand	Class B (Hwy/Mtn)	10
			Class C (Off-Hwy)	1
	Body		Class D (Off-Road)	0
Type:	End Du	ump	Maximum Grade:	6
Length (ft):		11.5	Wheelbase (in):	168
Height (ft):		12	Overhang (in):	50
Max Laden Weight	4	1000	Fr Axle to BOC (in):	69.5
(lbs):				
			Cab to Axle (in):	98.5
	Trailer		Cab to EOF (in):	148.5
No. of Trailer Axles:	\ *	0	Overall Comb. Length (in):	258
Type:				
Length (ft):		0	Special Req.	
Height (ft):		0	U.S. Domestic Registry, 50-state.	
Kingpin Inset (in):		0		
Comer Radius (in):		0		
	Restrictions			
Length (ft):		75		
Width (in):		102		
Height (ft):		13.5		
Approved by:			Date:	

Note: All sales are F.O.B. designated plant of manufacture.



Sales Code	Std/ Opt	Description	\$ List	Weigh
Model				
0000480	S	T480 Series Conventional	124,587	10,386
0071000	0	T480 Aero Hood	0	(
0080101	0	CARB Low NOX Omnibus Registration Guidelines	0	(
		Dealer/Customer acknowledges that this vehicle is NOT intended for		
		registration or domicile/primary use in the State of California.		
0080314	О	EPA Clean Idle Label - PACCAR PX Engines	36	11
0090161	0	T480 Single Rear	0	31
0098414	0	State of Registry: Indiana	0	
Engine 8	& Equi	pment		
0130221	0	PACCAR PX-9 330 330@1750 1000@1200, 2024	1,571	
3 8.500.0000 0		With Turbo Exhaust Brake (VGT Brake)		
		N09420 C333 0Reserve Speed Limit Offset (
		N09380 C334 0Maximum Cycle Distance (C334		
		N09360 C400 252Reserve Speed Function Reset		
		N09200 C399 100Standard Maximum Speed Limit		
		N09400 C401 10Maximum Active Distance (C40		
		N09220 C402 0Expiration Distance (C402)		
		N09540 C395 0Expiration Distance (C395)		
		N09260 C121 65Max Vehicle Speed in Top Gea		
		N09440 C234 YESEngine Protection Shtdwn		
		N09460 C231 NOGear Down Protection N09580 C133 5Idle Shtdwn Time		
		N09680 C233 YESIdle Shtdwn Override		
		N09480 C132 1400Max PTO Speed		
		N09300 C128 65Max Cruise Control Speed		
		N09500 C239 YESCruise Control Auto Resume		
		N09520 C238 NOAuto Engine Brake in Cruise		
		N09780 C190 80High Ambient Temperature Thr		
60		N09740 C188 40Low Ambient Temperature Thre		
		N09760 C189 60Intermediate Ambient Tempera		
		N09720 C382 YESEnable Hot Ambient Automatic		
		N09600 C396 YESEnable Impending Shutdown Wa		
		N09620 C397 60Timer For Impending Shutdown		
		N09640 C206 35Engine Load Threshold N09560 C225 NOEnable Idle Shutdown Park Br		
		N09560 C225 NOEnable Idle Shutdown Park Br		
1000046	0	EPA Emissions Warranty Engine	0	
1000151	S	PremierSpec	0	
1000243	0	Gearing Analysis: Performance	0	
	1078	power before economy results.		
1000254	0	Customer's Typical Operating Spd: 65 MPH	0	-

Price Level: January 1, 2025 Deal: Parry County Hvry Dapi Printed On: 7/2/2025 8:18:48 AM

100% Complete

Oate: July 02, 2025

Quote Number: QUO-1113838-K1J7M4



Sales Code	Std/ Opt	Description	\$ List	Weigh
1000344	0	EWI Tracking - A2 Engine Module Chassis	0	
1000525		RegistrationYear Year of Registration: 2025	0	(
1000684	0	Effective VSL Setting NA	0	(
1000858	0	Engine Idle Shutdown Timer Disabled	0	
1000859	0	Enable EIST Ambient Temp Overrule	0	(
1000891	0	Eff EIST NA Expiration Miles Use only with MX and Cummins engines	0	(
1002060	S	Air Compressor: Cummins 18.7 CFM For Cummins And PACCAR PX engines.	0	(
1041399	S	Air Cleaner: MD Composite Engine Mounted	0	(
1105231	S	Fan Hub: Horton On/Off for PX-9 or L9N	0	(
1121231	S	Cooling Module: 2.1M MD - Aero Hood 1000 Square Inches	0	(
1247263	0	EXH: Single Can 2024 RH Under with RH Side-of-Cab Vertical Tailpipe	1,217	(
1290124	0	Tailpipe: 5 in. single 24 in. 45 degree curved.	163	(
1321102	S	Fuel Filter: PACCAR 2.1M MD for PX-7 or PX-9 Fuel/water separator for 2021 and later engines.	0	C
1321205	0	Run Aid:Fuel Heat *For Fuel Filter	41	(
1321305	0	Start Aid:12V Heat *For Fuel Filter	22	•
1504006	0	Block Heater: PACCAR 750 watt 120V for PX-7 and B6.7N. 1000 watt for PX-9 and ISL9 Engines.	26	2
1816260	S	Alternator: PACCAR 160 amp, Brush Type	0	(
1821275	0	Batteries: 3 AGM GP31 THR (925) 2775 CCA. For T680, T880, or W990 in cab battery box only.	539	62
1836106	S	Mitsubishi 105P55 12V Starter with Cummins and PX PACCAR 12 volt electrical system. W/ centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded. Only for Cummins or PX engines.	0	(
1900996	0	Jump Start Terminals Under Hood.	85	(
1901018	S	Remote PTO/Throttle, 12-Pin, 250K, Back of Cab OR Back of Sleeper, J1939, Remote Control Provision	0	(
ıransmı	ssion	& Clutch		
2011631	0	Transmission: Allison 3500RDS 6-speed, With PTO	7,454	443

Price Level: January 1, 2025 Deal; Parry County Hwy Dept Printed On. 7/2/2025 8:18:48 AM

100% Complete

Date: July 02, 2025

Quota Number: QUO- H13662-K1J7M



Sales Code	Std/ Opt	Description	\$ List	Weight
	59-111 AE	drive gear. Limited to 1050LBFT. 6th Generation Controls. Includes heat exchanger & oil level sensor. Rugged Duty Series for vocational applications. Transynd transmission fluid is standard on all Allison 1000, 2000, 3000 & 4000 series transmissions.		
2401405	0	Driveline: 2 Dana Standard-Duty; 1 Centerbearing. *Standard duty is 1710 series.	39	-1
2409941	S	One Heavy-Duty One-Piece Aluminum Crossmember This option upgrades an existing crossmember. The cost does not include the centerbearing and bracket. Crossmember location will be in accordance with Kenworth engineering standards, using the major components specified on the DTPO.	0	(
2410018	0	Torque Converter Included W/ Allison Transmission.	0	(
2410114	0	Left Hand PTO Access, Right Hand Dip Stick Tube Allison 3000 series only.	42	(
2410153	0	Push Button Shifter Controls, Center Console Mounted for Allison Transmission. 2.1m Medium Duty only.	0	C
2410310	0	Allison Neutral at Stop	0	(
2410325	0	Allison Fuel Sense: ARM Base Economy	248	(
2410426	U	Allison RDS Package 223 Narr Allison RDS Package 223	0	(
2429358	0	Rear Transmission Support Springs for transmission PTO applications are required to ensure that engine flywheel housings are not overloaded when transmission PTO's are installed.	93	, (
2429378	0	Customer Installed Transmission PTO in the LH Mounted position (8 o'clock) for Allison 3000 & 4000 transmissions.	0	(
Front Ax	de & E	quipment	***************************************	
2513031	0	Meritor MFS14 Plus14.6K 3.5in. Drop Standard Track.	666	-282
2621310	S	Front Brakes: 14.6K Bendix ES S-Cam 16.5x5 in.	0	(
2659047	0	Front Dustshield: for Drum Brakes: All Front Axles.	58	(
2690002	S	Front Brake Drums: 14.6K 16.5x5 in. cast.	0	(
2690029	0	Drum Brake Knuckle for Use on Meritor MFS Plus Steer Axle	0	20
2702500	S	Front Hub: Iron Hub Pilot 14,600 lbs. 11-1/4 in. bolt circle. For use w/ air disc brakes. Consider wheelguards (5850002) w/ aluminum wheels.	0	(
2741970	S	ConMet PreSet Plus Hub Package; Front Axle.	0	(
2750001	S	Hubcap: Front Vented.	Ō	(
2765001	S	Front Auto Slack Adjuster for Drum Brakes.	0	(

Price Level: January 1, 2025 Geath Petry County Hwy Dept Printed On: 7/2/2025 8:18:43 AM 100% Complete

Oate: July 02, 2025

Quote Number QUO-1113888-K1J7M4



Sales Code	Std/ Opt	Description	\$ List	Weigh
2864072	0	Front Springs: Taperleaf 14.6K W/ Shock Absorbers	0	(
		w/ maintenance-free elastomer spring pin bushings.		
2895091	0	Single Power Steering Gear: 14.6K.	408	20
2900058	0	30 mm Front Suspension Spacer Block	0	C
2900612	0	Threaded Front Spring Bushings in Place of elastomeric.	66	0
Rear Ax	le & Ed	quipment	·····	-
3042160	s	Single Meritor RS23-160 Rear Axle rated at 23K.	0	0
3200563	S	Rear Axle Ratio - 5.63.	0	C
3330004	S	Single Rear Brakes 16-1/2x7 in. Bendix ES- extended service S-cam.	0	0
3392007	S	Single Rear Brake Drums: Cast S-Cam Single For use with 15x8.625", 16.5X7" or 16.5X8.625" brake.	0	0
3403220	S	Single Rear Hubs: Iron Hub Pilot 26k; 11.25" Bolt circle. Requires "R" series outer ends.	0	0
3441971	S	ConMet PreSet Plus Hub Package; Single Rear Axle.	0	0
3465001	S	Single Rear Axle Automatic Slack Adjusters. For use with drum brakes.	0	0
3485007	S	Spring Brake: 3030 Long Stroke Single 3 in. travel. For drum brakes. Helps keep brakes in adjustment longer.	0	0
3495226	S	Bendix 4S/4M Anti-Lock Brake System.	0	0
3511080	0	Meritor Driver Controlled Differential Lock for single rear axle.	812	0
3636430	0	Rear suspension: single Reyco 79KB taperleaf 23K with helper spring. Medium-duty. Unladen Height: 11.4 in. Laden Height: 9.7 in. Not available with rear air disc brakes.	608	57
3836315	S	Bolted Rear Suspension Crossmembers for Reyco 79KB. Replaces medium duty standard.	0	0
Tires & V	Wheels			
4080220	0	Front tires: Continental HSR3 12R22.5 16PR	531	66
4277487	0	Rear tires: Bridgestone M799 11R22.5 16PR. 42 in. diameter, drive. 19.5 in. SLR. Code is priced per pair of tires.	1,182	40
4900004	0	Rear Tire Quantity: 4	0	0
5045268	0	Front Wheel: Alcoa 89U63 22.5X9 AL Ultra One High Polish Wheel.	523	-39
5242268	0	Rear Wheel: Accuride 50885 22.5x8.25 steel Steel Armor[TM] powder coat, hub-pilot mount. Heavy-duty 5 hand-hole hub pilot mount. Code is priced per pair of wheels.	102	48
5853906	0	Powder Coat White Steel Wheel. Use in Conjunction	0	0

Price Level: January 1, 2025 Deal: Perry County Hwy Dept Printed On: 7/2/2025 8:18:43 AM Oate, July 02, 2025 Quote Numioan QUC-1113388-K1J7M4

100% Camaleie



Sales Code	Std/ Opt	Description	\$ List	Weigh
		with front, dual front, rear, spare or lift axle wheel code(s). All wheels on chassis must have same finish color.		
5900004	0	Rear Wheel/Rim Quantity: 4	0	
Frame &	Equi	oment		***************************************
6054250	S	Frame Rails: 10-5/8 x 3-1/2 x 5/16 in. Steel to 308 in. Truck frame weight is 2.91 lbin. per pair of rails. Section modulus is 14.80 cu.in., RBM is 1,776,000 in-lbs per rail. 120,000 PSI yield. Heat treated. Frame rail availability may be restricted based upon application, axle/suspension capacity, fifth wheel setting, or component/dimensional specifications. The results of the engineering review may result in a change to the requested frame rail. If a change is required, Kenworth Application Engineering will advise the dealer of the appropriate material specification for a substitute rail.	0	-60
6141200	0	Full Steel Insert: for 10-5/8 in. or 10-3/4 in. Steel to 284 in. or 2nd insert for 11-5/8 in. steel frame. Adds 1,149,000 lbin. to main rail RBM. Truck insert weight is 2.05 lbin. per pair of rails. Full frame insert length is equal to wheelbase plus rear frame cutoff plus dimension forward of front axle by model. See databook addendum section 7.2.	1,713	50
6309912	0	Delete Bumper: For Use With Provisions for customer-installed Braden winch bumper (2.1m MD) or heavy-duty front frame brackets for customer-installed winch bumper. Requires a bumper setting code.	0	
6319040	S	40 in. Bumper Setting. Requires a Bumper Code.	0	
6390077	0	Provisions for Customer-Installed Braden Winch bumper.	1,324	7:
6391203	0	Custom Frame Layout: 3-4 Chassis CFL DEF: NEED A THIRD CFS AREA - LH OUTSIDE AND LH BELOW RAIL ONLY. 26" CLEAR SPACE BEHIND THE DEF TANK.	375	
6397001	0	Huck Bolts Throughout Frame, where Possible.	0	
6405000	0	In-Cab Steel Battery Box: under Rider Seat or in stand alone box. Requires appropriate AGM battery code, which varies by model, and appropriate rider seat code be selected prior to entering the workscreen. Includes 1 battery disconnect switch.	1,300	
6409906	0	In-Cab Battery Box Location: Under Rider Seat.	0	
6451125	S	DPF/SCR Box Natural End Plates and Natural cover.	0	
6490139	S	Heavy-Duty One-PC Aluminum Intermediate/ Fill-In crossmember.	0	
6490433	S	Heavy-Duty 5-Piece Rear Cab Support, Hucked assembly. Huck fastened to frame.	0	
6497020	0	First Clear Frame Space Dimensioned from Back of Cab.	0	
6497030	0	Second Clear Frame Space Dimensioned from Back of Cab.	0	



Sales Code	Std/ Opt	Description	\$ List	Weigh
6497106	0	First - RH Outside and RH Below Rail Only.	0	
		Clear frame space area. Does not include fasteners or piping. Requires		
		a supplemental length and location code. Sales tool graphics do not		
		depict interference between requested location and other frame-		
		mounted components. The actual chassis layout will be determined at		
		time of engineering.		
6497116	0	Second - Between and Below Rails Only.	0	0
		Clear frame space area. Does not include BOC crossmember,		
		fasteners or piping. Requires a supplemental length and location code.		
		Sales tool graphics do not depict interference between requested		
		location and other frame-mounted components. The actual chassis		
0407000		layout will be determined at time of engineering.		
6497336	0	First - 36 in. Clear Frame Space Length.	0	0
		The impact to other frame-mounted components will be determined at		
0407544		time of engineering.		
6497514	0	Second - 14 in. Clear Frame Space Length.	0	0
		The impact to other frame-mounted components will be determined at		
0.400000		time of engineering.		
6498003	0	First clear space starting 3 in. behind cab	0	C
6499000	0	Second clear space starting 0 in. behind cab	0	0
6679806	0	Do Not Drive: Bumper is Deleted. Unit may be	0	0
		decked. Transporter review delivery options. Requires code 6309910 or		
		6309912.		
6679859	0	Final End-of-Frame Cut-Off Dimension Will be	0	0
		modified to 56 in. to 60 in.		
6679911	0	Component Restriction: Do Not Drive- Unit May be	0	0
6740000		decked.	400	45
6710080	0	Two Rams Horn Open Rear Tow Hooks, Not for trailer towing.	123	17
6721102	S	Rear Mudflap Arms: Betts B-25 Standard-Duty,	0	0
		straight. Includes B1732 mounting brackets as standard.		
6722000	S	Rear Mudflap Shields: White Plastic Antisail W/	0	0
		Kenworth logo.		
6742009	S	Square End-of-Frame W/O Crossmember; Non-Towing.	0	0
Fuel Tan	ks & E	Equip		
7140080	0	80 US Gallon D-Shape Rectangular Aluminum Under	362	52
/ 140000	O	fuel tank, replace. With non-slip step.	302	32
7722173	0	Large DEF Tank, 15 Gallons.	300	26
		-		
7889203	0	DEF to Fuel Fill Ratio 2:1 or Greater.	0	0
7889614	S	DEF Tank Location is LH BOC. For 2.1M Medium-Duty	0	0
7920080	0	Location: 80 gal fuel tank LH under cab	0	0
1320000	quipm			

Price Level: January 1, 2023 Deal: Perry County Hwy Dept Printed On: 7/2/2025 3:18:48 AM 100% Complete

Dats: July 02, 2025

Quote Number, OUO-1113838-K(1376/4



Sales Code	Std/ Opt	Description	\$ List	Weight
8024311	S	Cab: Stamped Aluminum with Curved Windshield	0	0
0000155		LED markers. Requires seperate roof code.	440	
8090155	0	Hood: Med Aero w/ Chrome Crown	112	0
8108002	0	Fine Particulate Filter for Cabin Air HVAC	35	0
		system. To provide extra filtration in high dust applications. Cabin airflow is reduced with this additional filter. *Cannot be used with code		
8108011	S	8108003. Cab HVAC - Day Cab and 40 in. Sleeper	0	0
0100011	J	System With Defrost, A/C, and 48,000 BTU/hr Heater. Includes		113
		automatic temperature control with one touch defrost operation and		
		dash mounted cab temperature and solar intensity sensors. Pleated		
		fresh air filter and cabin recirculation air filter standard. The Kenworth		
		HVAC system is designed to provide optimal heating and cooling in all		
		operating environments without need for additional insulation. Cab		
		HVAC without sleeper heater AC is available with 40in sleeper.		
8201047	0	Kenworth Smartwheel: 18 in. Non-Leather With	143	0
		Integrated Radio and Cruise Controls.		
8201200	S	Adjustable Telescoping Tilt Steering Column.	0	0
8203060	0	5 Sets of Keys. Replaces Standard 2 Sets of Keys.	34	0
	(8	,		
8203196	0	Dash Mounted Compact Trailer Brake Valve.	0	0
		Self Returning.		
8205135	0	Information for Customer-Installed PTO Muncie 10-bolt.	0	0
8205177	0	Dash Switch:1st Allison-Mounted PTO.	167	0
		Electric switch and wiring are factory-installed to control the 1st Allison		
0000400	_	Trans mounted PTO.	123	0
8208498	0	Five Spare Switches: Wired to Power.	123	U
8222409	0	Gauge: DD Virtual Gauge - Air Filter	0	0
		Restriction		
8222413	0	Gauge: DD Virtual Gauge - Manifold	0	0
		Pressure Boost		
8222414	0	Gauge: DD Virtual Gauge - Engine Percent	0	0
		Torque		
8222418	0	Gauge: DD Virtual Gauge - Engine Hours	0	0
3222.10		Instrument Cluster		t.
8222419	0	Gauge: DD Virtual Gauge - Volts	0	0
- Version edition and District		Instrument Cluster		
8282024	S	Main Instrument Package: 7" Digital Display	0	0
JZJZJZ4	0	Cluster. Includes Physical (Analog): Speedometer, Tachometer, Oil	•	•
		Pressure, and Coolant Temp; and Digital: Fuel Level #1, DEF Level,		
		DPF Filter Status, Fuel Economy, Volts Telltale, OAT and Primary Air		
		2. 1 1 mor ottato, 1 at Lorion, 1 totto fontato, 0/11 and 1 minuty / m		

Price Level: January 1, 2025 Deat: Perry County Hwy Cept Printed On: 7/2/2025 5:13:48 AM 100% Complete

0ata: July 02, 2025 Quota Number: 0UO -: 113888-K1J7W4



Sales Code	Std/ Opt	Description	\$ List	Weigh
		Pressure, Secondary Air Pressure, and Air Application for air brake trucks.	1014	
8282109	0	Large Flat Panel on Dash For C/I Controls. Replaces Storage Bucket.	12	(
8330591	S	Interior Trim Package: 2.1M MD Gray Foam Backing/Cloth Headliner W/Gray Sunvisor & Seat Color Three Underdash Center Console Cupholders (Two If Allison Transmission Is Selected).	0	C
8410122	0	Driver Seat: KW Air Seat HB Vinyl w/ Dual Armrests/Susp Cover	197	(
8450112	0	Rider Seat: KW Battery Box Seat HB Vinyl w/ Dual Armrests	-38	-25
8601432	0	Kenworth Radio DEA710 AM/FM/WB/USB, Bluetooth	405	C
8698965	0	Speaker Package For Cab: (2) Speakers B-Pillar	56	0
8699933	0	CB Installation Kit: C/I Center Mtd of Header w/ Dual Antenna on LH/RH mirrors. One Jumper Harness.	231	2
8700196	S	Turn Signal: Self-Cancelling	0	(
8700283	S	LH and RH Trip Ledge Rain Deflectors	0	(
8700601	S	Global Telematics Unit	0	
8800260	0	Long Grabhandle RH Side Mounted to Side-of-Cab exhaust.	31	2
8800372	0	Grabhandle: LH, Exterior, Side of Cab - Ergonomic Grab Handle Mounted To The Left Hand Exterior Of The Cab For Entry and Exit.	121	3
8800402	S	Dual Cab Interior Grabhandles: A Pillar Mounted Dash Wrap and B Pillar Mounted Grabhandles	0	C
8832113	S	Kenworth Daylite Door With Standard LH/RH electric door locks and LH/RH electric window controls.	0	0
8841642	0	Air Horn: Dual Round 26" LH/RH Roof Incl Air Horn Cover	234	Ö
8850139	S	Look-Down, Pass. Door, Black 11x6	0	0
8850842	S	Mirror Shell: Dual Aero In-Mold Black	0	C
8860852	0	Mirror: Dual KW Aero Rear View Motor, heated with Integral CX	66	C
8871446	S	Rear Cab Stationary Window 19in x 36in	0	C
8879917	0	Two Additional Outboard Windows 19in x 12in	149	10
8890038	0	3.5in x 11.5in Plastic Records Holder:Mounted On Rear Cab Panel. Not available With Sleeper Or 2 Person Bench Seat.	54	0

Price Level: January 1, 2026 Deal: Perty County Hwy Dept Printed On: 7/2/2025 8:18:48 AM



Sales Code	Std/ Opt	Description	\$ List V	/eigh
8890101	S	One-Piece Bonded-In Windshield With Curved Glass. Standard.	0	(
8890135	0	Exterior Stainless Steel Sunvisor.	720	11
8890874	0	Kenworth Cab Air Suspension.	160	(
8891011	0	Roof: Raised Profile, Stamped Aluminum w/ Additional Head Room & Interior Overhead Storage	306	(
Lights 8	Instru	uments		
9010803	S	Headlamps: Single Halogen Complex Reflector w/ Turn Indicator, Reflector and DRL. Fender Mtd.	0	(
9022130	0	Marker Lights: Five Rectangular LED. Chrome housing. For use with raised roof only. Required with exterior sunvisor.	62	(
9030052	S	LED Stop,Turn,Tail: With Two LED Backup Lights and With An LED License Plate.	0	(
9058085	0	Switch, Wire, Indicator Light: C/I Flood 1st SW Thru Grommet Under Cab	129	(
9080206	0	Switch & Wiring: Customer-Installed Beacon Lights with additional 20 ft jumper harness shipped loose.	203	ĺ
9090058	0	Switch & Wiring: For Customer-Installed Plow light. Includes circuit breaker.	156	(
9090151	0	Wiring:Cust. Install Trir Elec. Brake Controller. Class 8/T4 Content Includes Dash Signals: Ignition Power (20A), Ground, Stop Lamp and Electric Trailer Brake Controller Wired To EOF Junction Box. These Signals Are Located Near The NavPlus HD Area. No Need To Code For An Additional End of Frame Junction Box. EOF Junction Box Signals Are: Ground, Tail Lamp, Marker Lamp, Left Tum, Right Tum, Stop Lamp and Electric Trailer Brake Controller Wired To Dash. Medium Duty (not T4) Content Includes A MP 280 Series Connector In Dash Near Driver Door Connections With Signals: Battery Power (40A), Ground, Stop Lamp and Electric Trailer Brake Controller Wired To Chassis Connector. Medium Duty (not T4) 2 Way Deutsch Chassis Connector Located Near Back of Cab, With Signals: Ground and Electric Trailer Brake Controller Wired To Dash Connector.	156	4
9090180	0	Backup Alarm: Tail Light Bracket Mounted Variable self-adjusting 82-102 DBA.	134	C
9090316	0	Junction Box: End of Frame	235	1
9090849	0	Polyswitches Replacing Fuses. Switch Will automatically reset after removal of excess load.	43	C
Air Equi	pment			
9101219	0	Air Dryer: Bendix AD-HF Extended Purge Heated With Puraguard	31	C
9108001	S	Moisture Ejection Valve W/ Pull Cable Drain.	0	0
9110020	0	Full Truck Kit Gladhands mounted at end-of-frame. Seven-way female receptacle mounted at end-of-frame in taillamp bracket. Kit includes dash mounted	938	15
ca Lavali .	lanusio	TO THE RESIDENCE OF THE PROPERTY OF THE PROPER	Date. July 103) (2.5)

Price Level: January 1, 2025 Osal: Peny County Hwy, Dept Printed On: 7/2/2025 8:18:43 AM

100% Complete

Date. July 02, 2025

Quors Number: QUO nit 18883-K 1074/A



Sales Code	Std/ Opt	Description	\$ List	Weight
	2400	trailer air supply valve, trailer hand control valve, and hoses/fittings for the valves. Dash mounted parking brake valve, tractor protection valve, and spring brake inversion/relay valves are standard.		
9140020	S	Nylon Air Tubing in Frame & Cab, Excluding Hoses subject to excessive heat or flexing.	0	0
9140252	0	Locate Air Dryer Inside LH Rail BOC. This code requires the use of a custom frame layout code.	0	0
9140289	0	Air Tanks: Mounted Inside Frame Flanges where possible. This code requires the use of a custom frame layout code.	0	0
9140328	0	Trailer ABS Electric Supply Through SAE J560 7-pin connector per TMC RP137).	0	0
9150170	0	Air Tanks: Aluminum Replacing Steel All Tanks. *Not air tanks on lift axles.	369	-44
Extende	ed War	ranty		
9200008	S	Base Warranty - PACCAR PX-9 Engine 24 months / 250,000 miles / 402,336 km / 6250 hours.	0	0
9200022	0	Base Warranty - Standard Service Medium Duty 12 months / Unlimited miles & km	0	0
9210159	U	Sourcewell Narr Sourcewell Customer Sourcewell number: 141038	0	0
9210402	0	Allison 3000 Series Transmission Surcharge	700	0
9212661	0	TruckTech+ RD - 5YR Sub PACCAR PX Engines	799	0
9220001	0	Base Warranty: Emissions 5YR/100K MI - EPA Engine	0	0
Miscella	neous			
9409852	0	GHG Secondary Manufacturer: Does Not Apply	0	0
9490206	0	Warning Triangle Reflector Kit: Shipped Loose. Kit consists of 3 triangles in plastic carrying case. Not floor mounted.	58	4
9490404	0	One 5 lb. Dry Chemical Type Fire Extinguisher mounted outboard of driver seat. Class ABC.	136	11
9490645	0	Zinc Phosphate Frame Rail Paint Processing. Requires frame rail code. Code is for 1 pair of rails.	314	0
9490647	0	Zinc Phosphate Frame Insert Paint Processing. Requires any 1st frame insert code. Code is for 1 pair of any frame inserts.	314	0
9491652	S	EMUX Architecture	0	0
Promoti	ons			
9511124	0	Model Year 2025 Engine	0	0
Paint				
9700000	0	Paint Color Number(s).	0	0

Price Level: January 1, 2025 Deal: Parry County Hwy Dept Printed On, 7/2/2025 8,18:46 AM

100% Complete

Date: July 32, 2025

Quote Number: OUO-1113888-K1JZW-



Sales Code	Std/ Opt	Description	\$ List	Weight
		N9702 A - L0252 COKE RED	-	W
		N9720 FRAME N0001 BLACK		
9943004	S	Bumper Unpainted	0	0
9943051	0	Day Cab Premium Paint	621	0
9944820	S	1 - Color Paint - Day Cab	0	0
		Color will be White if no other color is specified.		
9965510	S	Base Coat/ Clear Coat.	0	0
		The Kenworth Color Selector contains additional instructions, as well as		
		information on Kenworth paint guidelines and surface finish		
		applications. Kenworth is standard with Dupont Imron Elite paint.		

Special Requirements

Special Requirement 1 0098025

Special Requirement 2

Special Requirement 3

Special Requirement 4

Order Comments

Total List Price (W/O Freight & Warranty &	\$153,833	
Surcharges)		
Marketing and Service Support Fee		\$1,555
Prepaid Freight		\$3,775
Total Surcharge/Options Not Subject To Discount		\$1,499
Total Weight (lbs)		11.436

Any price increase as the result of force majeure, rising costs of components (including but not limited to material shortages) or government tariffs are not included in the quoted price and will be the financial responsibility of the customer.

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can

Price Level: January 1, 2025 Deal: Perry County Hvry Dept Printed On: 7/2/2025 3:18,48 AM 100% Complete

Date: July 02, 2025

Quote Number: QUO-1113983-K1J7N4



occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information



Shipping Destinations

Intermediate Destination: NONE

Final Destinations	Quantity
Palmer Power 2929 South Holt Rd	3
Indianapolis, Indiana 46241	



Palmer Power & Truck Equipment 2929 South Holt Road • Indianapolis, IN 46241 Phone (317) 634-8951 Fax (317) 536-7240 www.palmerpowered.com

Ql	JOTE#: 25212 REVISION: A QUOTED BY: MEC Date	e: <u>06/13/25</u>	Date Revised:	06/12/25
^	FVANOVIUS TRUCK OFFITTE			
Cu	stomer: EVANSVILLE TRUCK CENTER Salesman: PETE V	WHITE	. Attn:	STEVE
Fn	d User: PERRY COUNTY Phone: (812) 843-3232	PO:		
L .	1 Hone. 1012/040-0202			
	YEAR MAKE MODEL VIN	1	MILEAGE	BED STOCK#
	2026 KENWORTH T480			
	DETAILS OF INSTALLATION			
	REPAIRS AND/OR REPLACEMENT	Labor	Parts	Sublet
	ISTALL SNOW & ICE PACKAGE			
-	INSTALL BEAU-ROC 11'6"X36"x42" DL DUMP BODY			
	SIDES ARE 5/32 HARDOX 450, FRONT IS 5/32 HARDOX 450			
	FLOOR AND TAIL GATE ARE 3/16 HARDOX 450, FLOOR SILL ARE 10 INCH			
\Box	DOMEX 100W 3/16". TAIL GATE IS DOUBLE ACTING, AIR REAEASE TAIL GATE			
	HYDRAULIC SYSTEM IS MUNCIE SYSTEM WITH CABLE CONTROLS AND			
	MUNCIE OESP3016 ELEC GRND SPDE SPREADER PACKAGE, CONTROL			
	TOWER IS 3 BANK CABLE CONTROL TOWER, , 35 GALLON SS VALVE TANK			
-	ENCLOSURE W/FILTER, WEATHER TIGHT LID, HOT/LOW OIL SENSOR PKG			
_	MOUNT BUYERS 18X18X24 ALUMINUM TOOL BOX LEFT SIDE	-		
-	INSTALL BUYERS 10'X42" TRIP EDGE PLOW WITH 4 INCH LIFT CYLINDER	 		
	INSTALL BUYERS QUCK HITCH ASSEMBLY WITH SWIVEL ADAPTOR INSTALL BUYERS 10'X57" 304SS SPREADER.	+		-
\dashv	INSTALL BUTERS 10 AST SU4SS SPREADER;			
ᅱ	NOTE: QUOTE INCLUDES HOOD MODIFICATION SO HOOD CAN BE			
_	OPENED WHEN PLOW IS ON UNIT:	+		
\dashv	0, 0,100 (1,100)	 		
\dashv				
1:7:	D PAINT			
AND DESCRIPTION OF THE PERSON	PAINT BED BLACK			er e
-	PAINT CODE N0001			
	D OPTIONS			The state of
T				
	BED TAILGATE SAFETY LOCKS		NO	
	BED TAILGATE COAL CHUTE(S)	N	O COAL CHUTE(S)
	VIBRATOR KIT		NO	
	SHOVEL HOLDER(S)		SHOVEL HOLDE	
4	GRAB HANDLE(S)		1 GRAB HANDLE	
27872				
	DRAULIC SYSTEM AND PLUMBING			
_	MUNCIE CABLE CONTROL SYSTEM WITH MUNCIE OESP3016F ELEC GRND SPEED SPREADER PACKAGE		VEO	
	ELEC GRIND SPEED SPREADER PACKAGE	-	YES	
+		 		
\dashv		 		
	CONTINUED ON BACKSIDE			
-	CONTINUED ON BACKSIDE			
111-	E CHAINS			
SHEET SHEET	ONSPOT TIRE CHAINS		No	
-+		 	110	

A COLLECK	
BUYERS MOUNTED ON LEFT 24X18X18	
TARP SYSTEM	
NO TARP SYSTEM INCLUDED	
TRAILER PACKAGE OPTIONS	
PINTLE HOOK PACKAGE	25 Ton Spring Loaded
TRAILER KIT PACKAGE	FACTORY
ELECTRIC BRAKE CONTROLLER	INCLUDED
LIGHTING PACKAGES	
AMBER OVAL LED CABSHIELD STROBES	NO
CLEAR OVAL LED CABSHIELD STROBES	NONE
AMBER OVAL LED REAR POST STROBES	YES
CLEAR OVAL LED REAR POST STROBES	NO
S/T/T BACKUP INTEGRATED LED TAILLIGHTS	YES
PATTERN LIGHTS	(2) Pattern Lights
HOOD PLOW LIGHTS	Hood LED Plow Lights
AMBER LED GRILL MOUNTED STROBES	(2) STROBES
CLEAR LED GRILL MOUNTED STROBES	NONE
AMBER/CLEAR LED GRILL MOUNTED STROBES	NONE
ROOF PLOW LIGHTS	
ROOF STROBE LIGHTS	No
Additional Options	
BODY UP LIGHT (PROX SWITCH)	l NO
*THIS QUOTE IS FOR CHASSIS WITH ALLISON TRANSMISSION	
*PALMER TO INSTALL AIR/CONTROLS TO OPERATE LIFT AXLE	
ANY ADDITIONAL SURCHARGE FEES INCURRED WILL CHANGE PRICE	
UP TILL PRODUCTION STATE DATE	
*QUOTE DOES NOT INCLUDE LABOR OR PARTS FOR RELOCATION	
OF CHASSIS COMPONENTS CAUSING INTERFERENCE	
*QUOTE DOES NOT INCLUDE SALES TAX	
*QUOTE DOES NOT INCLUDE FET	
	0 \$0.00
Reviewed by: Date:	
	Parts
Estimated prices are subject to change after a 15 day period. Additional parts and/or labor may	Sublet
be required, in which case the customer will be contacted prior to purchase and/or repair. For	Misc. Materials
questions, comments or concerns please contact Brian Faulkenberg at (866) 222-8741.	SUB TOTAL
I hereby authorize Palmer Fabricating to complete the above installations/ repairs:	Sales Tax
	F.E.T.
Customer Signature: Date:	GRAND TOTAL
ORDER IS SUBJECT TO 25% US TARIFF IF ENACTED ON 4/2/2025.	TARIFF
FURTHER DETAIL WILL BE PROVIDED ONCE AVAILABLE	TARIFF F.E.T.
	TOTAL PENDING TARIFF



Palmer Power & Truck Equipment 2929 South Holt Road • Indianapolis, IN 46241 Phone (317) 634-8951 www.palmerpowered.com

Warranty Table

		The Control of the Co
Muncie Power Products	1-Year (Allison World PTO's 2 Years)	Parts Only (No Labor)
Beau-Roc	2-Year	Parts and Labor (Established SRT times. Must be approved by Beau-Roc)
Mailhot Industries	G3 Series - 4 Year (Dump application only) G3 Series - 1 Year (Snow & Ice application)	Parts Partial Labor (\$225.00 covered) (Hydraulic oil and miscellaneous parts not covered)
Aero Industries, Inc.	6 Months	Parts Only (No Labor)
Apsco Power	1 Year	Parts Only (No Labor)
PPTE Workmanship	90 - Day	Parts and Labor (If failure deemed workmanship of Palmer Power & Truck Equipment)

Above warranty terms are manufacturer's warranty. Wa	rranty coverage is authorized/denied by manufacturer after review		
I hereby acknowledge the manufacturer's warranty terms from the above table:			
Customer Signature:	Date:		

		,